

MATERIAL SAFETY DATA SHEET

MSDS Name: Polyseamseal TUB & TILE ULTRA CLEAR CAULK
MSDS Number: DM460042
Version Number 2
Revision Date: OCT-13-2005
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: Polyseamseal TUB & TILE ULTRA CLEAR
CAULK
HMIS Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPE: B

Company Identification: HENKEL CONSUMER ADHESIVES
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class CAULK
Trade Name POLYSEAMSEAL
Product Code -- Clear

SECTION II - INGREDIENT AND HAZARD INFORMATION

| Hazardous Ingredient Name | CAS Number | Percent | TSCA |
|---------------------------|------------|---------|------|
|---------------------------|------------|---------|------|

No OSHA hazardous ingredients known at this time.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Milky-white caulk
Appearance/Color: CLEAR when dry
Solubility (in water): Yes
pH Value, +/- .3: 7.5
Boiling Range: 212.°F (100.°C)
Vapor Pressure (mmHg): 15.@ 68.°F (20.°C)
Evaporation Rate: 0.5 times Slower than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight Approx 36.%
% Volatile, Volume 40.%
Specific Gravity: 1.06
VOC (less H2O or exempt) <15 g/l, (1%)

MATERIAL SAFETY DATA SHEET

MSDS Name: Polyseamseal TUB & TILE ULTRA CLEAR CAULK
MSDS Number: DM460042
Version Number 2
Revision Date: OCT-13-2005
Page Number: 2

NOTE:

Odor : Mild acrylic odor. Freeze Point : 32 Deg F

SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)

Flammability Class N/A
Flash Range: Not Applicable
Explosive Range (LEL/UEL): Not Applicable

EXTINGUISHING MEDIA:

Dry chemical -- Carbon Dioxide -- Foam -- Water Fog
Will not burn in wet state.

SPECIAL FIRE-FIGHTING PROCEDURES:

Water may be used to cool and protect exposed containers.
Caution should be taken because uncured material is water soluble.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may burst when exposed to extreme heat or fire.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

Entry through Inhalation and Skin most likely

TARGET ORGANS...

None- No hazardous ingredients as per OSHA Regulations
CARCINOGENICITY...

NTP? N/A | IARC Monographs? N/A | OSHA? NO

EFFECTS OF OVEREXPOSURE

Inhalation: May cause nose or throat irritation.
Skin/Eye Contact: May cause irritation.
Ingestion: Swallowing large amounts may cause nausea, vomiting. (an unlikely route of entry)

FIRST AID MEASURES

Inhalation: If affected by inhalation, remove to fresh air.
Eye Contact: Flush with water for at least 15 minutes, and get prompt medical attention.
Skin Contact: Wash skin thoroughly with soap and water.
Ingestion: Drink water, and get medical attention.

N/A= Not applicable N/AV=Not available N/E, N/est=Not established

SECTION VI - STABILITY AND REACTIVITY

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

MATERIAL SAFETY DATA SHEET

MSDS Name: Polyseamseal TUB & TILE ULTRA CLEAR CAULK
MSDS Number: DM460042
Version Number 2
Revision Date: OCT-13-2005
Page Number: 3

INCOMPATABILITY:

None

CONDITIONS TO AVOID:

None

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce oxides of carbon and oxides of nitrogen when burned.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Wear appropriate protective clothing. Add dry absorbent and shovel or sweep up. Place in an appropriate container and seal.

WASTE DISPOSAL METHOD:

Dispose of in accordance with Federal, State, and Local regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

| ACGIH TLV | ACGIH TLV-C | ACGIH STEL | OSHA STEL | OSHA PEL |
|-----------|-------------|------------|-----------|----------|
|-----------|-------------|------------|-----------|----------|

RESPIRATORY PROTECTION:

NIOSH respirators recommended if vapors and mists are generated.

VENTILATION:

Local exhaust is recommended for safe practice.

PROTECTIVE CLOTHING:

Gloves and clothing should be worn to prevent repeated skin contact.

EYE PROTECTION:

Splashproof goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep from freezing. Keep away from heat.

Keep containers closed when not in use.

Avoid prolonged or repeated contact with skin.

Keep out of the reach of children.

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

GROUND TRANSPORT (DOT) - DOMESTIC

Caulking compound, Non Regulated

AIR TRANSPORT (DOT) - DOMESTIC

Caulking compound, Non Regulated

AIR TRANSPORT (IATA) - INTERNATIONAL

Caulking compound, Non Regulated

MATERIAL SAFETY DATA SHEET

MSDS Name: Polyseamseal TUB & TILE ULTRA CLEAR CAULK
MSDS Number: DM460042
Version Number 2
Revision Date: OCT-13-2005
Page Number: 4

MARINE - OCEAN TRANSPORT (IMDG)
Caulking compound, Non Regulated

SECTION X - REGULATORY INFORMATION:

Product is regulated by OSHA Hazard Communication standard (29CFR 1910.1200). However none of the five Hazard Categories (SARA 311, 312) are appropriate for this product.
SARA Section 313 toxic chemicals: NONE
All ingredients TSCA listed.
California PROP.65 Chemicals: none known

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.