



## PAINTER'S Caulk

### DESCRIPTION

Polyseamseal Painter's Caulk is a quality latex designed for interior applications. Painter's Caulk is a 100% acrylic base that seals out air, moisture, dirt and dust. Accepts minimal joint movement. Can be painted with oil or acrylic paints. Soap and water clean-up.

### FEATURES

- Soap and water clean-up
- Contains no silicone
- Permanently Flexible
- Low odor
- Paintable
- Easy to apply and tool
- 15 Year guarantee

### USES

Painter's Caulk is designed for interior use to seal cracks and gaps that are found around doors, baseboards and walls, molding, windows and wall joints. Can also be used for outdoor projects for less demanding projects. Bonds to wood, drywall, plaster, metals, brick, concrete, masonry, and painted surfaces.

### PACKAGING

- 12 – 10oz cartridges per case
- Product code – DM601042

### STORAGE

- Store in a dry place between 40°F (5°C) to 90°F (32°C).
- Shelf life is 12 months (unopened)

## TECHNICAL DATA

### COVERAGE

- ¼" diameter bead: Approx. 31 lin. ft./ 10oz cartridge
- 1/8" diameter bead: Approx. 132 lin. ft./10oz cartridge

### LIMITATIONS

- Apply at temperatures above 40°F (5°C) to 100F (49°C).
- Do not apply when rain or freezing temperatures are expected within 24 hours.
- Do not use for architectural joints, joints subject to heavy abrasion or tuck-pointing.
- Do not use below waterline, on aquariums, or to set mirror tiles.
- If joint depth exceeds 3/8" x 3/8" (9.5mm x 9.5mm).½" (12.7mm), use backing material.

### APPLICATION PROCEDURES

#### Preparation:

- Remove old Caulk. Silicone residue left on the surface will decrease adhesion
- Clean thoroughly to remove dirt, oil, wax, and loose paint.

### APPLICATION PROCEDURES

#### Directions:

- CUT tip on a slant to desired bead size.
- With caulk gun, apply steady trigger pressure forcing sealant onto the surface for a smooth bead.
- Smooth bead with wet finger or putty knife
- Wipe off excess with damp cloth before caulk dries.
- Paintable after 1 hour, depending on temperature and humidity.
- Allow 24 hours before exposing to water.

## **CLEAN-UP**

Clean tools and excess caulk with soap and water before caulking dries.

**VOC** = 32 g/l or 1.5% by wt.

**CAUTION! DO NOT TAKE INTERNALLY.  
KEEP FROM FREEZING.**

**KEEP OUT OF REACH OF  
CHILDREN.**

## **LIMITED 15-YEAR WARRANTY**

If within 15 years from the purchase date of this product, when used as directed, it cracks. Peels or separates, return sales receipt and used container to OSI Sealants, Inc., 7405 Production Drive, Mentor, Ohio 44060 for a product replacement. The seller will not accept liability for more than replacement. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE NOT EXPRESSLY SET FORTH HEREIN.

For consumer information, call Technical Services at (800) 624-7767

**OSI Sealants Inc.**

A Subsidiary of Sovereign  
Specialty Chemicals Inc.  
Mentor, Ohio 44060