



Tub & Tile Adhesive Caulk

DESCRIPTION

Tub & Tile Adhesive Caulk is a PVA based high performance caulk. This water-based caulk was designed for high humidity areas such as kitchens and bathrooms. Mildewcide has been added to resist unsightly mold & mildew growth on the cured caulk. Guaranteed to remain crack-proof and flexible, it provides a watertight seal around sinks, tubs and other fixtures. Tub & Tile also has the strength of an adhesive making it ideal for repairing loose tiles, molding and other materials around your home.

Tub & Tile Adhesive Caulk bonds to almost any surface including porcelain, ceramic, wood, concrete, metal, ceramic, drywall, plaster and much more. Easy to apply and tool. Environmentally safe, soap and water clean-up. Contains no silicone.

FEATURES

- Cured caulk will resist mold and mildew growth.
- Adhesive & Caulk in one
- Easy to apply & tool
- Remains flexible
- Soap & Water clean-up
- Low odor
- Water-resistant seal

USES

Tub & Tile Adhesive caulk was designed to be an adhesive and caulk in one. Ideal for setting sinks and sealing around tubs, backsplashes, countertops and other fixtures. Can also be used to repair loose and broken tiles.

LIMITATIONS

- Apply at temperatures above 40°F(5°C) but below 120°F(49°C).
- Do not apply outdoors when rain or freezing temperatures are expected within 24 hours.
- Do not use below water line or for aquariums, under shower door tracks
- Do not apply adhesive between non-porous surfaces.
- Do not use on mirrors.
- If joint size should exceed 1/4" x 1/4" use backing material.
- Not recommended for constant water immersion.

PACKAGING

- 12 – 10oz cartridges per case
- 12 – 6oz squeeze tubes per case
- 24 – 6oz squeeze tubes per case

COLOR OFFERING

- 10oz – White, Bone/Almond, Clear
- 6 oz – White, Bone/Almond and Clear

COVERAGE

- 1/4" round bead: Approx. 30 lin. ft/ 10oz cartridge
- 1/8" round bead: Approx. 122 lin. ft./10oz cartridge

STORAGE

- Protect from freezing. Store between 40°F(5°C) and 100°F(38°C)
- Shelf life is 12 months (unopened)

VOC-Colors <93g/l or 7.5%wt.
-Clear <2g/l or 1%wt.

APPLICATION PROCEDURES

Preparation

- Remove old caulk. Silicone remaining on surface will decrease adhesion.
- Clean thoroughly to remove dirt, grease, oil, wax, loose paint, dust and soap film.
- Remove mildew with bleach and detergent that does not contain ammonia. Rinse surface and allow to dry.

Directions:

- Cut tip on a slant to desired bead size.
- Insert cartridge in caulk gun.
- Apply steady pressure forcing caulk onto surface for a smooth bead.
- Smooth bead with wet finger or putty knife to desired appearance. Wipe off excess with damp cloth.
- Paintable in 2 hours, depending on temperature and humidity.
- Allow 24 hours before exposing to water.
- Periodically clean cured caulk with non-abrasive cleanser for best appearance.

Clean-up:

Clean tools and excess caulk with soap & water before caulk dries.

CAUTION! KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

LIMITED CRACK-PROOF WARRANTY

If within 1 year from the date of purchase this product, when used as directed, cracks, peels or separates, return sales receipt and used container to OSI Sealants Inc, 7405 Production Drive, Mentor, Ohio 44060 for product replacement. The seller will not accept liability for more than product replacement. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE NOT EXPRESSLY SET FORTH HEREIN.

For additional information, please contact Technical Services 1-800-624-7767.

OSI[®]**OSI Sealants Inc.**

A Subsidiary of
Sovereign Specialty
Chemicals, Inc.
Mentor, Ohio 44060

Made in USA

Phone: 800-624-7767

Fax: 440-974-8774

www.polyseamseal.com

sD20615